

TRACK	Bedworth (Outdoor tarmac)
DATE	27-08-2008
CONDITIONS	Dry and cool
RESULT	18 / 313
FASTEST LAP	16.72

ITEM	SETTING
FRONT SUSPENSION	
SHOCK SPRINGS	Blue (FTD Models)
SHOCK OIL	40wt
SHOCK POSITION	Outer
RIDE HEIGHT	3.5mm
DROOP	8mm
CAMBER	2.0
CASTER	6
TOE	0
ROLL CENTRE	Inner raised 1.5mm
REAR SUSPENSION	
SHOCK SPRINGS	Red (FTD Models)
SHOCK OIL	60wt
SHOCK POSITION	Middle
RIDE HEIGHT	4.0mm
DROOP	10mm
CAMBER	1.5
ANTI-SQUAT	Kit
TOE	3.0
ROLL CENTRE	Kit
WHEELBASE	Shortest
DRIVE	
MOTOR	Dynamite 8400
GEARING	16/56 (44mm tyres)
FRONT DIFF	Geared
REAR DIFF	Geared
GENERAL	
CELLS	Intellect 1600
CELL POSITION	Forwards
BODYSHELL	Mazda 6
TYRES	45
ADDITIVE	None

Note: Use longer front shock shafts on rear as well to achieve desired droop.