

TRACK	Leamington (Indoor carpet. Tight and twisty)
DATE	Base indoor setup
CONDITIONS	High grip
RESULT	~30 laps
FASTEST LAP	~10 seconds

ITEM	SETTING
FRONT SUSPENSION	
SHOCK SPRINGS	Blue (FTD Models)
SHOCK OIL	40wt
SHOCK POSITION	Outer
RIDE HEIGHT	1.5mm
DROOP	4mm
CAMBER	1.0
CASTER	6
TOE	0
ROLL CENTRE	Inner raised 1.5mm
REAR SUSPENSION	
SHOCK SPRINGS	White (FTD Models)
SHOCK OIL	40wt
SHOCK POSITION	Outer
RIDE HEIGHT	1.5mm
DROOP	5mm
CAMBER	1.5
ANTI-SQUAT	Kit
TOE	3.0
ROLL CENTRE	Kit
WHEELBASE	Shortest
DRIVE	
MOTOR	Dynamite 8400
GEARING	12/56
FRONT DIFF	Geared
REAR DIFF	Geared
GENERAL	
CELLS	Intellect 1600
CELL POSITION	Rearwards
BODYSHELL	Mazda 6
TYRES	45 (small diameter)
ADDITIVE	Nosram. Full rear, half front

Note: remove screw shock collars to get ride height down (use plastic spacers instead).